



LISTING INFORMATION OF Therma Tru 20 Min (without hose) Fiberglass Fire Door PP  
Model 20PPFFD

SPEC ID: 25542

Therma Tru Corporation  
1750 Indian Wood Circle  
Maumee, OH 43537

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Fiberglass Reinforced Faced (Proprietary Core) (Simulated Panel Type or Flush) Swinging Door for installation in up to 20 minute locations (with or without hose stream-see table below). For use in any "Category C - Standard" frames. These doors may also be installed in frames listed in "Category C - Proprietary" in accordance with the frame manufacturer's individual listing.

**Limitations**

Cylindrical/Deadbolt/Latches with maximum 2-3/4" backset/Mortise Latch/Card Reader/Surface Mounted Vertical Rod Fire Exit Devices/Rim-Type Fire Exit Devices/Viewers/Protection Plates/Surface Mounted Closers/Surface or Kerf Mounted Door Bottom/ Arch Top and Round Top Door Configurations.

**Maximum Size of Openings**

Single Swing (**without hose stream**) 3'0" wide x 8'0" high

Standard and Double Egress Pairs - Not Allowed

**Testing Standard**

UBC-7-2-97, UL-10C (Positive Pressure) (2009), NFPA 252 (2008).

All assemblies are identified by a label or marking bearing the wording, "Listed (Product)", a time interval, temperature rise (if applicable), a serial number and the WHI Certification Mark.

(Unless otherwise specified, all Fire Doors have a nominal thickness of 1-3/4".)

<u>Attribute</u>	<u>Value</u>
CSI Code	08 10 00 Doors and Frames
CSI Code	08 15 00 Plastic Doors
Fire Resistance	20 Min w/out Hose Positive Pressure
Swing	Single Swing
Listed or Inspected	LISTED
Report Number	100354358MID-001
Criteria	NFPA 252 (2008)
Criteria	UL 10(c) (2009)
Intertek Services	Certification
Listing Section	CATEGORY A - DOORS - NO ADDITIONAL EDGE-SEALING SYSTEM REQUIRED