



LISTING INFORMATION OF

**Therma Tru 20 Minute Positive Pressure Fiberglass Skin  
Foam Core Fire Door without Hose Stream (20PPFFCWOH)**

SPEC ID: 48999

Therma Tru Corporation  
1750 Indian Wood Circle  
Maumee, OH 43537  
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## LISTING INFORMATION

Fiberglass Reinforced Faced (Proprietary Core) (Simulated Panel Type or Flush) Swinging Door for installation in up to 20 minute locations (without hose stream - see below). For use in any "Category C - Standard" frames. These doors may also be installed in frames listed in "Category C - Proprietary" in accordance with the frame manufacturer's individual listing.

### Limitations

Cylindrical/Deadbolt/Latches with maximum 2-3/4" backset/Mortise Latch/Card Reader/Surface Mounted Vertical Rod Fire Exit Devices/Rim-Type Fire Exit Devices/Viewers/Protection Plates/Surface Mounted Closers/Surface or Kerf Mounted Door Bottom.

### Maximum Size of Openings

Single Swing (**without hose stream**) 3'0" wide x 8'0"high

Standard and Double Egress Pairs - Not Allowed

### Testing Standard

UL-10C (Positive Pressure), NFPA 252

All assemblies are identified by a label or marking bearing the wording, "Listed (Product)", a time interval, temperature rise (if applicable), a serial number and the WHI Certification Mark.

(Unless otherwise specified, all Fire Doors have a nominal thickness of 1-3/4".)

Attribute	Value
Criteria	UL 10(c) (2016)
Criteria	NFPA 252 (2017)
CSI Code	08 10 00 Doors and Frames
CSI Code	08 15 00 Plastic Doors
Fire Resistance	20 Min w/out Hose Positive Pressure
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	CATEGORY B - DOORS - ADDITIONAL EDGE-SEALING SYSTEM REQUIRED
Report Number	G103875182
Spec ID	48999
Swing	Single Swing
Test Original Issue Date	05/01/2019
Verification Testing	No