	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

***** Section 1 - Product and Company Identification *****

Manufacturer/Importer Information

Therma-Tru Corporation
 108 RE Jones Road
 Butler IN, 46721

Emergency Phone: CHEMTREC,U.S.:(800) 424-930
 International: (703) 527-3887 (703) 527-3887

Product Identifier

50-11914

Recommended Use

Restrictions on Use

***** Section 2 – Hazards Identification *****

GHS Classification

- FLAMMABLE LIQUIDS - Category 2
- SKIN CORROSION/IRRITATION - Category 2
- CARCINOGENICITY - Category 2
- TOXIC TO REPRODUCTION (Fertility) - Category 2
- TOXIC TO REPRODUCTION (Unborn child) - Category 2
- SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS Label Elements


Symbol(s)



Signal Word - Danger

Hazard Statements

Highly flammable liquid and vapor.
 Causes skin irritation.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL		Revision Date: 8-26-2015

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

May cause drowsiness and dizziness.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

Response

IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention.

Storage

Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.


*** Section 3 – Composition / Information on Ingredients ***

Substance/mixture

Mixture

Other means of identification

Not Available

	<h2>Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015
		Revision Date: 8-26-2015

CAS #	Component	Percent
108-88-3	toluene	79.72%
1330-20-7	xylene, mixed isomers	10.90%
100-41-4	ethyl benzene	2.56%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

*** Section 4 – First Aid Measures ***

First Aid: Eyes

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

First Aid: Skin


Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

First Aid: Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

First Aid: Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or

	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

Causes serious eye irritation.

Inhalation

Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

Skin contact

Causes skin irritation

Ingestion

Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact

Adverse symptoms may include the following:

Pain or irritation

Watering

Redness.

Inhalation

Adverse symptoms may include the following:

Nausea or vomiting

Headache

Drowsiness/fatigue

Dizziness/vertigo

Unconsciousness


Reduced fetal weight

Increase in fetal deaths

Skeletal malformations.

Skin contact

Adverse symptoms may include the following:

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

Irritation
 Redness
 Reduced fetal weight
 Increase in fetal deaths
 Skeletal malformations

Ingestion

Adverse symptoms may include the following:
 Reduced fetal weight
 Increase in fetal deaths
 Skeletal malformations.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

***** Section 5 – Fire Fighting Measures *****


Extinguishing Media

Suitable Extinguishing Media

Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable Extinguishing Media

Do not use water jet.

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

Specific hazards arising from the chemical

Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous Thermal Decomposition Products

Decomposition products may include the following materials:
 Carbon dioxide
 Carbon monoxide
 Halogenated compounds.

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

***** Section 6 – Accidental Release Measures *****


Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.


Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

*** Section 7 – Handling and Storage ***

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure -obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.


***** Section 8 – Exposure Controls / Personal Protection *****

Component Exposure Limits

Name (CAS #)	OSHA - PEL	ACGIH - TLV
toluene	CEIL: 500 ppm TWA: 200 ppm 8 hours. STEL: 300 ppm 15 minutes.	TWA: 20 ppm 8 hours.
xylene, mixed isomers	TWA: 100 ppm 8 hours.	TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes
ethyl benzene	TWA: 100 ppm 8 hours	TWA: 20 ppm 8 hours. STEL: 125 ppm 15 minutes.

Engineering Measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures


Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Selection of personal protective equipment (PPE) is to be established by the employer performing a PPE hazard assessment. In the U.S.A, OSHA requires completion of a documented PPE hazard assessment as described in 29 CFR 1910.132.

Eye/face Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

	<h2>Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015
		Revision Date: 8-26-2015

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

* * * Section 9 – Physical & Chemical Properties * * *

Appearance:	Not Available	Odor:	Not Available
Physical State:	Liquid	pH:	Not Available
Vapor Pressure:	Not Available	Vapor Density:	1.56 @ 32°F (0°C)
Boiling Point:	109 - 140 °C (228.2 - 284 °F)	Melting Point:	Not Available
Solubility (H2O):	Not Available.	Specific Gravity:	Not Available
Evaporation Rate:	Highest known value: Greater than 1. (toluene) compared with butyl acetate	Density:	0.881 g/cm ³
Vapor Pressure:	5.1 mm Hg (0.6783 kPa) (Highest known value: xylene, mixed isomers)	Flash Point:	Closed cup: 4°C (39.2°F)
Vapor Density:	> 1 (Air = 1) (Calculation)	Upper	8%

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

	method)	Flammability Limit (UFL):	
Lower Flammability Limit (LFL):	1.2%	Volatility:	94.44% (w/w)

***** Section 10 – Chemical Stability & Reactivity Information *****

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability

This is a stable material.

Hazardous Reaction Potential

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid


Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible Products

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

***** Section 11 – Toxicological Information *****

Acute Toxicity

Product/Ingredient Name	Result	Species	Dose	Exposure
Toluene	LC50 inhalation vapor	Rat	49000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12124 mg/kg	-
	LD50 Oral	Rat	636 mg/kg	-
Xylene, mixed isomers	LC inhalation vapor	Rat	5000ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Ethyl benzene	inhalation vapor	Rat	55000 mg/m ³	2 hours
	LD50 Dermal	Rabbit	15486 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Carcinogenicity

Classification


Product/ingredient name	OSHA	IARC	NTP
ethyl benzene	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Product/Ingredient	Result	Species	Dose	Exposure
Toluene	Positive Unreported	Mammal –species unspecified	-	-

	<h2>Safety Data Sheet</h2>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015
		Revision Date: 8-26-2015

Specific target organ toxicity (single exposure)

Product/Ingredient	Category	Route of exposure	Target organs
Toluene	3	NA	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not Available.

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential Acute Health Effects

Eye contact :

Causes serious eye irritation

Inhalation :

Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

Skin contact :

Causes skin irritation.

Ingestion :

Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.


Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Adverse symptoms may include the following: pain or irritation, watering, redness

Inhalation

Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations

	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

Skin contact

Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations

Ingestion

Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects

Not available

Potential delayed effects

Not available

Long term exposure

Potential immediate effects

Not available

Potential delayed effects

Not available

Potential chronic health effects

Not available

General No known significant effects or critical hazards.


Carcinogenicity Suspected of causing cancer. Risk of cancer depends on duration and level of exposure

Mutagenicity No known significant effects or critical hazards

Teratogenicity Suspected of damaging the unborn child.

Developmental effects No known significant effects or critical hazards.

Fertility effects Suspected of damaging fertility.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

***** Section 12 – Ecological Information *****







Data available upon request


***** Section 13 – Disposal Considerations *****

Waste Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

***** Section 14 – Transportation Information *****

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	Paint related material	Paint related material	Paint related material	Paint related material	Paint related material	Paint related material
Transport hazard class(es)						
Packing group	II	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.	No.
Additional - - information	Reportable quantity 917.41 lbs /			Special provisions 640 (C)		

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

	416.5 kg [124.89 gal / 472.76 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.		Tunnel code (D/E)
--	--	--	--------------------------

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

***** Section 15 – Regulatory Information *****


U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act (CAA) 112 regulated toxic substances: toluene; xylene, mixed isomers; ethyl benzene; chlorobenzene

SARA 313

	Product name	CAS number	%
Form R-Reporting requirements	Toluene	108-88-3	79.72
	Xylene, isomers mixed	1330-20-7	10.90
	Ethyl benzene	100-41-4	2.56

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State Regulations

Massachusetts: None of the components are listed

New Jersey: None of the components are listed

New York: None of the components are listed

Pennsylvania: None of the components are listed

California Prop 65: **WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Toluene	No	Yes	No	No
Ethyl benzene	Yes	No	No	No

Canada Inventory: At least one component is not listed.

International Regulations

Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

Japan inventory: Not determined.

Korea inventory: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan inventory (CSNN): Not determined.

Chemical Weapons Convention List Schedule Chemicals:


Not listed

Chemical Weapons Convention List Schedule II Chemicals:

Not listed

Chemical Weapons Convention List Schedule III Chemicals:

Not listed

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Issue Date: 6-30-2015 Revision Date: 8-26-2015

***** Section 16 – Other Information *****

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.

1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.


The customer is responsible for determining the PPE code for this material

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	Product Name: PF-1G-ADH : Adhesion Promotor-1 GAL	Revision Date: 8-26-2015

Disclaimers

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

Language for consideration:

Information presented in this Safety Data Sheet for the product(s) described in Section 1 ("Product") has been compiled from sources considered to be dependable, accurate, and reliable, but manufacturer/importer does not guarantee the accuracy of any information presented. Except as expressly provided otherwise in a written contract executed by manufacturer/importer, to the fullest extent permitted by applicable law, manufacturer/importer disclaims, and the recipient or user of this safety data sheet ("recipient") hereby expressly waives, any and all warranties, whether express, implied or statutory, with respect to the product or this safety data sheet, and any results or effect obtained from their use by recipient and/or other users, including, without limitation, any statutory or implied warranties of merchantability or fitness for a particular purpose. Manufacturer/importer specifically, but not by way of limitation, disclaims any and all liability for the use or performance of the product or safety data sheet by recipient, recipient's customers and/or other users.