	<b>Safety Data Sheet</b>	SDS No. 50-11914
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Issue Date: 6-30-2015
		Revision Date: 1-18-2016

**\*\*\* Section 1 - Product and Company Identification \*\*\***

**Manufacturer/Importer Information**

Therma-Tru Corporation  
108 RE Jones Road  
Butler IN, 46721

Emergency Phone: CHEMTREC,U.S.:(800) 424-930  
International: (703) 527-3887 (703) 527-3887

**Product Identifier**

**630-279**

**Recommended Use**

**Restrictions on Use**

**\*\*\* Section 2 – Hazards Identification \*\*\***

**GHS Classification**

CARCINOGENICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract) -  
Category 1

**GHS Label Elements**

**Symbol(s)**




**Signal Word - Danger**

**Hazard Statements**

Suspected of causing cancer.  
Corrosive to the respiratory tract.

**Precautionary Statements**

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear eye or face protection. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

### Response


IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

### Storage

Store locked up. Store in a well-ventilated place. Keep cool.

### Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**\*\*\* Section 3 – Composition / Information on Ingredients \*\*\***

**Substance/mixture**

Mixture

**Other means of identification**

Not Available

CAS #	Component	Percent
13463-67-7	Titanium dioxide	
67-56-1	Methanol	
980-26-7	Quinacrodone pigment	
111-76-2	2-butoxyethanol	
112-34-5	2-(2-butoxyethoxy)ethanol	
1897-45-6	tetrachloroisophthalonitrile	
1333-86-4	carbon black	
7664-41-7	Ammonia	
124-68-5	2-amino-2-methylpropanol	
7631-86-9	synthetic amorphous silica	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.**


**\*\*\* Section 4 – First Aid Measures \*\*\***

**First Aid: Eyes**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**First Aid: Skin**

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

### First Aid: Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### First Aid: Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

#### Eye contact

No known significant effects or critical hazards.

#### Inhalation


Exposure to decomposition products may cause a health hazard. Serious effects be delayed following exposure.

#### Skin contact

No known significant effects or critical hazards

#### Ingestion

No known significant effects or critical hazards

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**Over-exposure signs/symptoms**

**Eye contact**

No specific data.

**Inhalation**

No specific data.

**Skin contact**

No specific data.

**Ingestion**

No specific data.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**

No specific treatment.

**Protection of first-aiders**

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**See toxicological information (Section 11)**

**\*\*\* Section 5 – Fire Fighting Measures \*\*\***


**Extinguishing Media**

**Suitable Extinguishing Media**

Use dry chemical, CO2, water spray (fog) or foam.

**Unsuitable Extinguishing Media**

Do not use water jet.

	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**Specific hazards arising from the chemical**

Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous Thermal Decomposition Products**

Decomposition products may include the following materials:  
 Carbon dioxide  
 Carbon monoxide

**Special protective actions for fire-fighters**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**\*\*\* Section 6 – Accidental Release Measures \*\*\***


**Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders**

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

### Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.


#### Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

<b>*** Section 7 – Handling and Storage ***</b>
---

### Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure -obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities


Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**\*\*\* Section 8 – Exposure Controls / Personal Protection \*\*\***

### Component Exposure Limits

Name (CAS #)	OSHA - PEL	ACGIH - TLV
Methanol (67-56-1)	TWA: 200 ppm 8 hours.	TWA: 200 ppm 8 hours. STEL: 250 ppm 15 minutes.
2-butoxyethanol (111-76-2)	TWA: 50 ppm 8 hours.	TWA: 20 ppm 8 hours.
carbon black (1333-86-4)	TWA: 3.5 mg/m <sup>3</sup> 8 hours.	TWA: 3 mg/m <sup>3</sup> 8 hours
Ammonia (7664-41-7)	TWA: 50 ppm 8 hours.	TWA: 25 ppm 8 hours. STEL: 35 ppm 15 minutes
Synthetic amorphous silica (7631-86-9)	TWA: 80 mg/m <sup>3</sup> 8 hours.	TWA: 10 mg/m <sup>3</sup> 8 hours.



	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

### Engineering Measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures


Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Selection of personal protective equipment (PPE) is to be established by the employer performing a PPE hazard assessment. In the U.S.A, OSHA requires completion of a documented PPE hazard assessment as described in 29 CFR 1910.132.

#### Eye/face Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures,

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection


Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**\*\*\* Section 9 – Physical & Chemical Properties \*\*\***

<b>Appearance:</b>	Not Available	<b>Odor:</b>	Not Available
<b>Physical State:</b>	Liquid	<b>pH:</b>	9 to 9.5
<b>Boiling Point:</b>	65 - 172 °C (149 - 341.6 °F)	<b>Melting Point:</b>	Not Available
<b>Solubility (H2O):</b>	Not Available.	<b>Specific Gravity:</b>	Not Available
<b>Evaporation Rate:</b>	Highest known value: Greater than 1. (toluene) compared with butyl acetate	<b>Density:</b>	1.221 g/cm <sup>3</sup>
<b>Vapor Pressure:</b>	17.5 mm Hg (2.3275 kPa) (Highest known value: water)	<b>Flash Point:</b>	Closed cup: >93.3°C (>199.9°F) [Product does not sustain combustion.]

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

<b>Vapor Density:</b>	< 1 (Air = 1) (Calculation method)	<b>Upper Flammability Limit (UFL):</b>	8%
<b>Lower Flammability Limit (LFL):</b>	Not Available	<b>Volatility:</b>	51.35% (w/w)

<b>*** Section 10 – Chemical Stability &amp; Reactivity Information ***</b>
---

**Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**Chemical Stability**

The product is stable.

**Hazardous Reaction Potential**

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to Avoid**


No specific data.

**Incompatible Products**

No specific data.

**Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**\*\*\* Section 11 – Toxicological Information \*\*\***

**Acute Toxicity**


Product/Ingredient Name	Result	Species	Dose	Exposure
methanol	LC50 Inhalation vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5600ppm	-
2-butoxyethanol	LC50 Inhalation vapor	Rat	450 ppm	4 hours
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
2-(2-butoxyethoxy) ethanol	LD50 Dermal	Rabbit	15486 mg/kg	2 hours
	LD50 Oral	Rat	3500 mg/kg	-
tetrachloroisophthalonitrile	LC50 inhalation vapor	Rat	220 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	10000 mg/kg	-
ammonia	LC50 Inhalation vapor	Rat	2000 ppm	4 hours
	LD50 Dermal	Rat	4840 mg/kg	-
	LD50 Oral	Rat	350 mg/kg	-
2-amino-2-methylpropanol	LD50 Oral	Rat	2900 mg/kg	-
synthetic amorphous silica	LD50 Dermal	Rabbit	7500 mg/kg	-
	LD50 Oral	Rat	3160 mg/kg	-

**Irritation/Corrosion**

Not available.

**Sensitization**

Not available.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

## Carcinogenicity

### Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
tetrachloroisophthalonitrile	-	2B	-
carbon black	-	2B	-

IARC has issued a notice that they will publish a monograph that lists titanium dioxide (TiO<sub>2</sub>) as possibly carcinogenic to humans (Group 2B) by inhalation (based solely on animal data). Human epidemiology studies do not suggest an increased risk of cancer in humans for occupational exposure to titanium dioxide. According to the IARC summary on titanium dioxide, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

## Reproductive toxicity

Not available.

## Teratogenicity


Product/Ingredient	Result	Species	Dose	Exposure
tetrachloroisophthalonitrile	Positive	Mammal– species unspecified	-	-

## Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
titanium dioxide	3	NA	Respiratory tract Irritation
Tetrachloroisophthalonitrile	3	NA	Respiratory tract Irritation
synthetic amorphous silica	3	NA	Respiratory tract Irritation

## Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Methanol	1	Not determined	central nervous system (CNS) and optic nerve

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**Aspiration hazard**

Not available

**Information on the likely routes of exposure**

Not available.

**Potential Acute Health Effects**

**Eye contact :**

No known significant effects or critical hazards.

**Inhalation :**

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Skin contact :**

No known significant effects or critical hazards.

**Ingestion :**

No known significant effects or critical hazards.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact**

No known significant effects or critical hazards

**Inhalation**

No known significant effects or critical hazards

**Skin contact**

No known significant effects or critical hazards

**Ingestion**


No known significant effects or critical hazards

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

**Potential immediate effects**

Not available

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**Potential delayed effects**

Not available

**Long term exposure**

**Potential immediate effects**

Not available

**Potential delayed effects**

Not available

**Potential chronic health effects**

Not available

**General** Causes damage to organs through prolonged or repeated exposure.

**Carcinogenicity** Suspected of causing cancer. Risk of cancer depends on duration and level of exposure

**Mutagenicity** No known significant effects or critical hazards.

**Teratogenicity** No known significant effects or critical hazards.

**Developmental effects** No known significant effects or critical hazards.

**Fertility effects** No known significant effects or critical hazards.


**\*\*\* Section 12 – Ecological Information \*\*\***

Data available upon request

**\*\*\* Section 13 – Disposal Considerations \*\*\***

**Waste Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered

	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

<b>*** Section 14 – Transportation Information ***</b>
--

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-	-	-	-	-
<b>Transport hazard class(es)</b>	-	-	-	-	-	-
<b>Packing group</b>	-	-	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.	No.	No.
<b>Additional - - information</b>	-	-	-	-	-	-

**Special precautions for user**

**Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**


Not available

<b>*** Section 15 – Regulatory Information ***</b>
--

**U.S. Federal regulations**

**United States inventory (TSCA 8b):** All components are listed or exempted.



	<h1 style="margin: 0;">Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

**Clean Air Act (CAA) 112 regulated toxic substances:** 2-(2-butoxyethoxy)ethanol;  
methanol

**SARA 313**

	Product name	CAS number	%
Form R-Reporting requirements	methanol 2-butoxyethanol	67-56-1 111-76-2	2.40 1.45

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State Regulations**

Massachusetts: None of the components are listed

New Jersey: None of the components are listed

New York: None of the components are listed

Pennsylvania: None of the components are listed

California Prop 65: **WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
titanium dioxide	Yes	No	No	No
methanol	No	Yes	No	No
tetrachloroisophthalonitrile	Yes	No	No	No
carbon black	Yes	No	No	No

Canada Inventory: At least one component is not listed.

**International Regulations**

Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.


Japan inventory: Not determined.

Korea inventory: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

	<h1>Safety Data Sheet</h1>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

Taiwan inventory (CSNN): Not determined.

**Chemical Weapons Convention List Schedule Chemicals:**  
Not listed

**Chemical Weapons Convention List Schedule I Chemicals:**  
Not listed

**Chemical Weapons Convention List Schedule III Chemicals:**  
Not listed

**\*\*\* Section 16 – Other Information \*\*\***

**Hazardous Material Information System (U.S.A.)**

Health	*	3
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.

1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material

**National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

	<h2 style="margin: 0;">Safety Data Sheet</h2>	SDS No. 50-11914
		Issue Date: 6-30-2015
	<b>Product Name: PF-1G-BC6 : Basecoat 6 – 1 GAL</b>	Revision Date: 1-18-2016

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### **Disclaimers**

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

### ***Language for consideration:***

Information presented in this Safety Data Sheet for the product(s) described in Section 1 (“Product”) has been compiled from sources considered to be dependable, accurate, and reliable, but manufacturer/importer does not guarantee the accuracy of any information presented. Except as expressly provided otherwise in a written contract executed by manufacturer/importer, to the fullest extent permitted by applicable law, manufacturer/importer disclaims, and the recipient or user of this safety data sheet (“recipient”) hereby expressly waives, any and all warranties, whether express, implied or statutory, with respect to the product or this safety data sheet, and any results or effect obtained from their use by recipient and/or other users, including, without limitation, any statutory or implied warranties of merchantability or fitness for a particular purpose. Manufacturer/importer specifically, but not by way of limitation, disclaims any and all liability for the use or performance of the product or safety data sheet by recipient, recipient’s customers and/or other users.